



- NOTES:**
1. WHEN NATURAL LEADS OF MAGNETICS ARE NOT USED, CHARGER COMPONENTS ARE CONNECTED WITH BLACK FLAME-RETARDANT SWITCHBOARD INSULATION SYSTEM (SIS) TYPE WIRING, IDENTIFIED ON EACH END WITH NUMBER-CODED MARKERS. GROUND WIRES ARE GREEN WITH YELLOW STRIPE.
  2. FOR MOUNTING OF PC BOARDS (A7, A4, ect.) SEE PAGE 2 OF JE5253-99.

REV. 0	DRN BY KJB	CHK BY MCR	APP BY MCR	DATE 1/21/2020	DRN BY KJB	DATE 1/21/2020
DESCRIPTION				STANDARD DRAWINGS.	CHK BY MCR	DATE 1/21/2020
PROPERTY AND CONFIDENTIAL NOTICE				ANY REPRODUCTION, PARTIAL OR AS A WHOLE OF THIS DOCUMENT WITHOUT THE WRITTEN PERMISSION OF HINDLE POWER, INC IS STRICTLY PROHIBITED.		

	<b>HINDLEPOWER</b>		1075 Saint John Street Easton, PA 18042-6661 PH 610-330-9000 FAX 610-330-8510 www.hindlepowerinc.com	
	<b>TITLE</b> ATEVO BATTERY CHARGER CONN DIAGRAM: 6-50ADC WITH COMMON OPTIONS			
<b>B</b>	SCALE NTS	DWG No JE5255-99	REV 0	SHEET 1 OF 2

